



GDM-351A HANDHELD DIGITAL MULTIMETER



FEATURES

- Manual Ranging (22 ranges)
- Continuity Beeper/Diode Test
- Overload Protection
- hFE Measurement
- Resistance Measurement up to 200MΩ
- Battery Check (9V, 1.5V)
- HC31 Carry Case (option)

SPECIFICATION

<i>DC Voltage:-</i>	Range	200mV, 2V, 20V, 200V, 600V 5 ranges
	Accuracy	± (0.5% rdg + 1 digit)
	Input Impedance	10MΩ
<i>AC Voltage (50Hz ~ 500Hz):</i>	Range	200mV, 2V, 20V, 200V, 600V 5 ranges
	Accuracy	± 1.0% rdg ~ ± 1.5% rdg depends on range
	Input Impedance	10MΩ
<i>DC Current:</i>	Range	200μA, 2mA, 20mA, 200mA, 10A 5 ranges
	Accuracy	± 1.0% rdg ~ ± 2.0% rdg depends on range
<i>AC Current (50Hz ~ 500Hz):</i>	Range	200μA, 2mA, 20mA, 200mA, 10A 5 ranges
	Accuracy	± 1.2% rdg ~ ± 2.0% rdg depends on range
<i>Resistance:</i>	Range	200Ω, 2kΩ, 20kΩ, 200kΩ, 2MΩ, 20MΩ, 200MΩ 7 ranges
	Accuracy	± 0.8% rdg ~ ± 5.0% rdg depends on range
<i>Continuity Beeper:</i>	Buzzer sounds if conductance less than 100Ω	
<i>Diode Test:</i>	Test Current	1mA ± 0.6mA
	Open Voltage	3.0V typical
<i>Transistor hFE Test:</i>	Range	0 ~ 1000 hFE
	Base Current	Approx. 10μA, (Vce=3V)
<i>Display:</i>	3 1/2 digits LCD display	
<i>Power Source:</i>	Single 9V battery, NEDA 1604, JIS 006P, IEC 6F22	
<i>Accessories:</i>	Instruction manual, Test lead, Battery, HC31 Carry Case (Option)	
<i>Dimensions & Weight:</i>	84(W) × 157(H) × 37(D) mm, 250g	
<i>Ordering Information:</i>	GDM-351A: Handheld Digital Multimeter	
	HC-31: Carry Case for DMM	