

Hi-Pot Testers

GWINSTEK

GPI / T-800 Series



- 500VA AC Capacity (GPT-805, GPT-815, GPI-825).
- True RMS Current Readback.
- Arc Detect.
- Digital Display of Voltage, Current & Timer Simultaneously.
- 9-Pin Remote Control for Start & Reset.
- Alarm Lamp & Buzzer for Fail Indication.

		GPT-805	GPT-815	GPI-825	GPI-826
ACW Test	DC Output Voltage V Regulation V Accuracy Trip Current, mA Current Accuracy	0.1 ~ 5kV 15% ± 3% Reading ± 3 Counts 0.3 ~ 100mA 3% of Reading ± 2 Counts			0.1 ~ 5kV 15% ± 3% Reading ± 3 Counts 0.3 ~ 20mA 3% of Reading ± 2 Counts
DCW Test	AC Output Voltage V Regulation V Accuracy Trip Current, mA Current Accuracy	Non. Non. Non. Non. Non.	0.1 ~ 5kV 20% ± 3% Reading 0.3 ~ 10mA 3% of Reading	Non. Non. Non. Non. Non.	
IR Test	Output Voltage V Regulation V Accuracy	Non. Non. Non.		DC 500V / 1000V 1 ~ 2000MΩ 1 ~ 500M: 5% of Reading 501M 2000M: 10% of Reading	
General	Test Time Arc Detection Digital Display 9-Pin PLC Remote Control Display	1 ~ 180sec / Continual 0.3 ~ 100mA V, A, Time Yes 3½ Digits 0.39" LED			1 ~ 180sec / Continual 0.3 ~ 20mA V, A, Time Yes 3½ Digits 0.39" LED
	Power Source Dimensions Weight	AC115V or 230V, 50/60Hz, Setup by Manufacturer 330mm (W) x 149mm (H) x 446mm (D) 15kg (GPI-826 12kg)			
Standard Accessories		Power Cord x 1, Instruction Manual x 1, Test Lead; GHT-105 x 1			

ORDERING INFORMATION

GPI-825	Electrical Safety Tester.	GPI-826	Electrical Safety Tester.
GPT-815	Electrical Safety Tester.	GPT-805	Electrical Safety Tester.

Tel: +44 (0)20 8868 1311 Fax: +44 (0)20 8866 6596
1-3 Kildare Close, Eastcote, Ruislip, Middlesex HA4 9UR

